

MTP850 Ex

ATEX TETRA Terminals

High performing communication and user safety



Key Features

High Performing Communication

- Strong rugged design for optimum reliability in harsh conditions
- Powerful, high quality audio in most demanding environments
- Full range of supporting ATEX certified accessories to tailor customize solution

Comprehensive User Safety

- ATEX & IEC-Ex gas and dust approvals
- Integrated GPS for user location
- Internal "Man Down" alarm

Part of Motorola's market leading range of ATEX TETRA terminals, the MTP850 Ex provides high quality communication with comprehensive user safety and class leading ATEX specifications allowing use when in environments containing potentially explosive gas and dust.

Motorola is a world leader in the development and deployment of TETRA communication solutions, and the MTP850Ex ATEX TETRA radios deliver safe and reliable communications for users with a powerful set of features to harness the capability of TETRA.

High Performance Communication

The MTP850Ex delivers best in class audio performance in the typical noisy environments where specialist users from industry or public safety operate.

Comprehensive User Safety

The MTP850Ex can be used in explosive gas and dust environments due to its high level of protection.

Operational safety is further enhanced with a range of features including:

- State of the art integrated GPS receiver providing the ability to locate personnel through the radio, improving user safety and resource management.
- Internal "Man Down" alert this fully integrated solution triggers an emergency procedure when the carrier of the radio remains motionless far a set period or falls down.

Simple but Powerful User Interface

The simplified keypad with large button surface makes the MTP850Ex radios easy to use with gloves. Combined with the large scalable display fonts and icons, the MTP850Ex facilitates operation in difficult environments with limited visibility.

Data Applications Capability

The integrated WAP browser and Multi-Slot packet data enables rapid access to critical information in the field. Applications are further enhanced with ability to have simultaneous Short Data Service (SDS) and Multi-Slot packet data services via TNP1 protocol.

ATEX SPECIFICAT	TONS			
	ATEX Rating		IEC Ex Rating	
	Gas	Dust	Gas	Dust
MTP850Ex-2D	II 2G Ex ib IIC T4	II 2D Ex ibD 21 IP6x T90°C	Ex ib IIC T4 (Approved for Zone 1 & 2, Equipment Group II, Gas Group C, Temperature Class T4, -20°C to +50°C)	Ex ibD 21 IP6x T90°C (Approved for Zone 21 & 22, Equipment Group II)
Specification	ons			

PHYSICAL	PHYSICAL			ENVIRONMENTAL SPECIFICATIONS		
Dimensions (mm)		135 x 55 x 38		-20°C to	+50°C (Hazardous Environments)	
Weight (typ) g		400	Operating Temperature (°C)	-20°C to +60°	C (Non-Hazardous Environments)	
Battery		725 mAh, 7,2V	Storage Temperature (°C)	-4	0°C to +85°C (MIL STD 810 C, D)	
		12 hrs, typ, 5/5/90 duty cycle	Humidity	E	TS 300 019-1-5 Class 5.1 and 5.2	
			Dust and Water		IP64	
RF SPECIFICATI	ons		Shock, drop and vibration		ETS 300 019-1-5 Class 5M2	
Frequency Bands (M	IHz)	380 – 430				
Switching Bandwidth (MHz)		50	GPS SPECIFICATIONS			
RF Channel Bandwid		25	Simultaneous Satellites		12	
Transmitter RF Power		1W	Mode of Operation		Autonomous or assisted (A-GPS)	
RF Power Control	Ï	3 Steps of 5 dB	GPS Antenna		Integrated in TETRA antenna	
RF Power Level Accuracy		+/- db 2	Sensitivity		-152 dBm / -182 dBW	
Receiver Class		A & B	Accuracy	5 meter (50% probal		
Receiver Static Sensitivity (dBm)		-112 minimum, -115 typical	Location Protocols	ETSI		
Receiver Dynamic S	ensitivity (dBm)	-103 minimum, -107 typical			Motorola LRRP	
VOICE SERVICE	S		DATA SERVICES			
Talkgroups	2048 (TMO) & 1024	(DMO)	Status Messaging	Alias Messages	100	
Phone Book	1000 persons		Short Data Service (SDS)	Inbox	20 messages	
Scan Lists	40 lists, 20 talkgroup	s / list		Target Address	Individual or Group Address	
TMO Services	Group Call	Late entry		Voice Interaction	Send / receive during calls	
	Private Call	Half / Full Duplex	Packet Data	Single or Multi Slot	7.2kbps - 28.8 kbps gross	
	Telephony	Full Duplex	WAP	Integrated Openwave b	rowser	
	DGNA	up to 2047 groups		WAP 1.2.x and WAP 2.0 compatibility for UDP/IP Stack		
DMO Services	Group Call	Late entry	PEI	AT Commands		
DIVIO GELVICES	Private Call			TNP1; enables simultar	neous SDS & PD	
DIVIO GELVICES	Filvate Call					
DINO GENICES	Compatibility	Gateway & Repeater				

	Filvate Call	riali / r uli Duplex
	Telephony	Full Duplex
	DGNA	up to 2047 groups
DMO Services	Group Call	Late entry
	Private Call	
	Compatibility	Gateway & Repeater
Emergency	Smart Emergency	DMO / TMO / DMO to TMO
	Hot Mic	Configurable timers
	Location	Send on emergency
	Target Address	Individual or Group
	Alarm	Emergency Status
Other Services		Ambience Listening

Other Services Ambience Listening Transmit Inhibit		, (CCK % G	
INTERFACES		Network Access	Temporary Enable / Disable (Stun) Permanent Enable / Disable (Kill)
RS232 PEI	For connection of data devices	Authentication	Infrastructure initiated and made mutual by terminal
Rugged Accessory	For programming and audio accessory connectivity		

PERIPHERALS	AND	ACCESSORIES

Audio	A wide range of audio accessories is available including ATEX certified speaker mics and headsets.
Power & Charging	Solutions for desk top charging and multi-way chargers
Carrying	A range of carrying solutions is available including carry cases, carry strap and belt clips
Programming	Comprehensive solutions available for radio configuration and encryption key loading via Motorola KVL,

Air Interface Encryption

Key Provisioning



Algorithms

Security Classes

TEA1, TEA2, TEA3

Class1 (clear), Class2 SCK), Class3 (DCK, CCK & GCK*)

Secure provisioning tool (key variable loader KVL)