

SPECIFICATION SHEET
REL. 04-00

POINT-TO-POINT 300 SERIES RADIOS



PTP 300 Integrated



PTP 300 Connectorized

SPECIFICATION SHEET

5.4 AND 5.8 GHZ POINT-TO-POINT BRIDGES – PTP 300 SERIES

RADIO TECHNOLOGY	REMARKS
RF band	5.725 GHz–5.875 GHz ¹ 5.470 GHz–5.725 GHz ¹
Channel size	Configurable to 5, 10 or 15 MHz
Channel selection	By <i>intelligent</i> Dynamic Frequency Selection (<i>i</i> -DFS) or manual intervention; automatic selection on start-up and continual adaptation to avoid interference
Transmit power	Varies with modulation mode and settings from -18 dBm to 27 dBm
System gain	Integrated: Varies with modulation mode; up to 167 dB using 23 dBi integrated antenna ² Connectorized: Varies with modulation mode and antenna type ²
Receiver sensitivity	Adaptive, varying between -94 dBm and -69 dBm
Modulation	Dynamic; adapting between BPSK and 64 QAM
Error correction	FEC
Duplex scheme	Symmetric Fixed TDD; same or split frequency Tx/Rx where regulations permit
Antenna	Integrated: Integrated flat plate 23 dBi / 8° Connectorized: Can operate with a selection of separately-purchased single and dual polar antennas through 2 x N-type female connectors (check local regulations prior to purchase)
Range	Up to 155 miles (250 km); up to 6 miles (10 km) in the optional LOS mode
Security and encryption	Proprietary scrambling mechanism; optional FIPS-197 compliant 128-bit and 256-bit AES Encryption

ETHERNET BRIDGING & T1/E1

Protocol	IEEE 802.3
User data throughput	Standard—Dynamically variable up to 25 Mbps at the Ethernet (aggregate): 5 MHz Channel – Up to 13 Mbps 10 MHz Channel – Up to 25 Mbps 15 MHz Channel – Up to 25 Mbps (Upgradable to a PTP 500; requires a license-key purchase) LOS Mode—Dynamically variable up to 50 Mbps at the Ethernet (aggregate): 5 MHz Channel – Up to 18 Mbps 10 MHz Channel – Up to 35 Mbps 15 MHz Channel – Up to 50 Mbps (Optional, requires a license-key purchase)
Latency	<3 ms average each direction
QoS	802.1p (4 levels)
Interface	10 / 100 Base T (RJ-45) – auto MDI/MDIX
T1/E1 interface	Single T1/E1 port (with splitter cable); G703/G704, G823/G824

MANAGEMENT & INSTALLATION

LED indicators	Power status, Ethernet link status and activity
System management	Web or SNMP v1/v2c/v3 using MIBII and a proprietary PTP MIB; Motorola Wireless Manager, version 2.2 or higher
Installation	Built-in audio and graphical assistance, plus voltage output for link optimization
Connection	Distance between outdoor unit and primary network connection: up to 330 ft. (100 meters)
Lightning protection	Built into the Outdoor Unit (ODU); an external PTP Lightning Protection Unit (PTP-LPU) end device is required near the base of the tower or wall at the cable entrance point leading to the network to protect the indoor LAN equipment

PHYSICAL

Dimensions	Integrated ODU: Width 14.5" (370 mm), Height 14.5" (370 mm), Depth 3.75" (95 mm) Connectorized ODU: Width 12.2" (309 mm), Height 12.2" (309 mm), Depth 4.1" (105 mm) Powered Indoor Unit (PIDU Plus): Width 9.75" (250 mm), Height 1.5" (40 mm), Depth 3" (80 mm)
Weight	Integrated ODU: 11.8 lbs (5.35 kg) including bracket Connectorized ODU: 10.4 lbs (4.7 kg) including bracket PIDU Plus: 1.9 lbs (864 g)
Wind speed survival	202 mph (325 kph)
Power supply	Integrated with Indoor Unit
Power source	90–240 VAC, 50–60 Hz / 36-60V DC; redundant powering configurations supported
Power consumption	50 W max

ENVIRONMENTAL & REGULATORY

Operating temperature	-40°F (-40°C) to +140°F (+60°C), including solar radiation
Protection and safety	UL60950-1; IEC60950-1; EN60950-1; CSA-C22.2 No. 60950-1
Radio	5.8 GHz: USA CFR 47 Part 15.247 Canada IC RSS-210 Issue 7 Europe EN 302 502, Eire Comreg 06/47R, UK IR2007 5.4 GHz: USA CFR47 Part 15.407 Europe EN 301 893, Canada IC RSS-210 Issue 7
EMC	USA CFR 47 Part 15 Class B Canada CSA Std C108.8 1993 Class B Europe EN 55022 CISPR 22, Europe EN 301 489 - 1/4

¹ Regulatory conditions for RF bands may vary by geographic location and should be confirmed prior to system purchase.

² Gain, maximum transmit power and effective radiated power may vary based on regulatory domain.